Claims

1.   A method for identifying to a user an object from a
digitally captured image thereof whose image characteristics are
present in at least one database including:
      decomposing the digitally captured image into a group of
parameters; and
      comparing each of said group of parameters with identical
parameters of known objects stored in the at least one database;
and
      producing the best matches from the at least one database to
a user to identify the object.

2.   The method as defined in claim 1 further including before
decomposing the digitally captured image:
      determining if the digitally captured image includes at least
one symbolic image, and if such is included;
          decoding the at least one symbolic image;
          comparing the decoded at least one symbolic image to a
database of decoded symbolic images; and
          determining a level of confidence that the object has
been identified.

3.   The method as defined in claim 2 further including:
      reducing the database choices in accordance with the
determined level of confidence with which said comparing each of
said group of parameters with identical parameters of known
objects stored in the at least one database is performed.

4.   The method as defined in claim 1 wherein the at least one
database includes:
      URLs associated with the objects, and wherein said method
includes:

5   establishing a connection between an URL associated with the
6 identified object and the user.

1   5.   The method as defined in claim 1 wherein the at least one
2 database includes:
3   operative devices for interaction with the user when
4 identified as the object.

1   6.   The method defined in claim 1 wherein the decomposing the
2 digitally captured image into a group of parameters includes:
3   performing a radiometric correction of the digitally captured
4 image by:
5   transforming the digitally captured image to one of a
6 set of digital numbers per color plane, RGB representation; and
7   normalizing in all color planes with linear gain and
8 offset transformations so that pixel values within each color
9 channel span a full dynamic range of the set.

1   7.   The method defined in claim 6 wherein the decomposing the
2 digitally captured image into a group of parameters after a
3 radiometric correction includes:
4   analyzing the radiometrically normalized RGB image for
5 regions of similar color, and
6   mapping region boundaries formatted as an x, y binary image
7 map of the same aspect ratio as the radiometrically normalized RGB
8 image.

1   8.   The method defined in claim 7 wherein the decomposing the
2 digitally captured image into a group of parameters after mapping
3 region boundaries of similar color includes:
4   grouping regions in increasing number to produce a plurality
5 of groups.

9. The method defined in claim 8 wherein for each group of regions:

generating a bounding box by:

determining the elliptical major axis of the segment group of an ellipse just large enough to include the entire segment group; and

determining a rectangle with long sides parallel to the elliptical major axis of a size just large enough to completely contain every pixel in the segment group.

10. The method defined in claim 9 wherein for each generated bounding box:

converting all pixels not included in the generated bounding box to a mid-level gray; and

remapping such that the corners of the bounding box are mapped into the corners of an output test image for comparison to the at least one data base.

11. The method defined in claim 10 wherein for each output test image:

producing a high grayscale thereof by:

adding proportionately each R, G, and B pixel of the output test image by:

using the following formula:

$$L_{x,y} = 0.34*R_{x,y} + 0.55*G_{x,y} + 0.11*B_{x,y};$$ and then

rounding to nearest integer value.

12. The method defined in claim 10 wherein for each output test image:

transforming the RGB image into a normalized Intensity (Y), In-phase (I) and Quadrature-phase (Q) color image;

averaging the Y, I, and Q values for each segment; and

saving Y_{avg} = Average Intensity,

7   I_{avg} = Average In-phase,

8   Q_{avg} = Average Quadrature,

9   Y_{sigma} = Intensity standard deviation,

10   I_{sigma} = In-phase standard deviation,

11   Q_{sigma} = Quadrature standard deviation,

12   N_{pixels} = number of pixels in the segment, for each

13 segment as a three-dimensional color space map.

1   13. The method defined in claim 12 wherein for each three-
dimensional color space map:
        extracting:
            the region outer edge boundary;
            the total area enclosed by the region outer edge
boundary;
            the area centroid of the total area enclosed by the
region outer edge boundary; and
            the net ellipticity of the closest fit ellipse to the
region.

1   14. The method defined in claim 12 wherein for each output test
2 image:
3   subsampling the output test image to produce a low resolution
4 grayscale by:
5   combining a number of pixels in both x and y directions,
6 and saving the brightness result at a reduced dynamic range.

1   15. The method defined in claim 11 wherein for each output test
2 image:
3   transforming the RGB image into a normalized Intensity (Y),
4 In-phase (I) and Quadrature-phase (Q) color image;
5   averaging the Y, I, and Q values for each segment; and
6   saving Y_{avg} = Average Intensity,
7   I_{avg} = Average In-phase,
8   Q_{avg} = Average Quadrature,

9 Y_{sigma} = Intensity standard deviation,

10 I_{sigma} = In-phase standard deviation,

11 Q_{sigma} = Quadrature standard deviation,

12 N_{pixels} = number of pixels in the segment, for each

13 segment as a three-dimensional color space map.

1   16.   The method defined in claim 15 wherein for each three-

2 dimensional color space map:

3   extracting:

4   the region outer edge boundary;

5   the total area enclosed by the region outer edge

boundary;

7   the area centroid of the total area enclosed by the

region outer edge boundary; and

9   the net ellipticity of the closest fit ellipse to the

10 region.

1   17.   The method defined in claim 16 wherein for each output test

2 image:

3   subsampling the output test image to produce a low resolution

4 grayscale by:

5   combining a number of pixels in both x and y directions,

6 and saving the brightness result at a reduced dynamic range.

1   18.   The method defined in claim 17 wherein each determined

2 output:

3   comparing each against the at least one database; and

4   producing best matches from the at least one database.

1   19.   The method defined in claim 18 wherein each determined

2 output are compared against the at least one database in parallel.

1 20. The method defined in claim 18 wherein each determined
2 output are compared against the at least one database in
3 combinations.

1 21. The method defined in claim 18 wherein the at least one
2 database is indexed and each determined output are compared
3 against the at least one database in indexed areas thereof which
4 contain similar data to the determined output.

1 22. A method for identifying to a user a multi-dimensional
2 object from at least one digitally captured image thereof whose
3 image characteristics are present in at least one database
4 including:
   decomposing the at least one digitally captured image into a
5 group of parameters of different types; and
   comparing the parameters of each type of the group of
6 different parameter types with parameters of matching types of the
7 different parameter types of known objects stored in the at least
8 one database; and
11 producing a parameter match to a user from at least one
12 parameter type, with respect to the at least one database for a
13 high probability identification of the object.

1 23. The method defined in claim 22 wherein the producing a
2 parameter match to a user from at least one parameter type, with
3 respect to the at least one database for a high probability
4 identification of the object includes:
5 producing the best parameter match from a plurality of
6 parameters.

1 24. The method defined in claim 22 wherein the producing a
2 parameter match to a user from at least one parameter type, with

3   respect to the at least one database for a high probability

4   identification of the object includes:

5   producing the best match from at least one group of a

6   plurality of parameter types.

1   25.   The method defined in claim 22 wherein the decomposing the

2   digitally captured image into a group of parameters of different

3   types includes:

4   performing a radiometric correction of the at least one

5   digitally captured image by:

6   transforming the at least one digitally captured image

7   to at least one of a set of digital numbers per color plane, RGB

8   representation; and

9   normalizing in all color planes with linear gain and

10   offset transformations so that pixel values within each color

11   channel span a full dynamic range of the set.

1   26.   The method defined in claim 25 wherein the decomposing the

2   at least one digitally captured image into a group of parameters

3   of different types after a radiometric correction includes:

4   analyzing the radiometrically normalized RGB image for

5   regions of similar color, and

6   mapping region boundaries formatted as an x, y binary image

7   map of the same aspect ratio as the radiometrically normalized RGB

8   image.

1   27.   The method defined in claim 26 wherein the decomposing the

2   at least one digitally captured image into a group of parameters

3   of different types after mapping region boundaries of similar

4   color includes:

5   grouping regions in increasing number to produce a plurality

6   of groups.

1   28.   The method defined in claim 27 wherein for each group of

2   regions:

3   generating a bounding box by:

4   determinining the elliptical major axis of the segment

5   group of an ellipse just large enough to include the entire

6   segment group;

7   determining a rectangle with long sides parallel to the

8   elliptical major axis of a size just large enough to completely

9   contain every pixel in the segment group;

10   converting all pixels not included in the generated

11   bounding box to a mid-level gray; and

12   remapping such that the corners of the bounding box are

13   mapped into the corners of an output test image for comparison to

14   the at least one data base.

1   29.   The method defined in claim 28 wherein for each output test

2   image:

3   producing a high grayscale thereof by:

4   adding proportionately each R, G, and B pixel of the

5   output test image by:

6   using the following formula:

7            $L_{x,y} = 0.34*R_{x,y} + 0.55*G_{x,y} + 0.11*B_{x,y}$; and then

8   rounding to nearest integer value.

1   30.   The method defined in claim 28 wherein for each output test

2   image:

3   transforming the RGB image into a normalized Intensity (Y),

4   In-phase (I) and Quadrature-phase (Q) color image;

5   averaging the Y, I, and Q values for each segment; and

6   saving Y_{avg} = Average Intensity,

7   I_{avg} = Average In-phase,

8   Q_{avg} = Average Quadrature,

9   Y_{sigma} = Intensity standard deviation,

10   I_{sigma} = In-phase standard deviation,

11   Q_{sigma} = Quadrature standard deviation,

12   N_{pixels} = number of pixels in the segment, for each
13   segment as a three-dimensional color space map.